

UMORE



CLASSICO

(4 OF 5) CERAMIC WALL TILES


CLASSICO

(4 OF 5) CERAMIC WALL TILES


UMORE



3X6 WALL TILES



SIMPLY WHITE
UMOSIWH4CL36G



SIMPLY WHITE MATTE
MOSIWH4CL36M



GRACEFUL GRAY
UMOGRGR4CL36G



GRACEFUL GRAY MATTE
UMOGRGR4CL36M




TAUPE
UMOTAUP4CL36G




TAUPE MATTE
UMOTAUP4CL36M


3X12 WALL TILES




SIMPLY WHITE
UMOSIWH4CL312G




SIMPLY WHITE MATTE
UMOSIWH4CL312M



GRACEFUL GRAY
UMOGRGR4CL312G



GRACEFUL GRAY MATTE
UMOGRGR4CL312M



TAUPE
UMOTAUP4CL312G




TAUPE MATTE
UMOTAUP4CL312M


4X10 WALL TILES



SIMPLY WHITE
UMOSIWH4CL410G




SIMPLY WHITE MATTE
UMOSIWH4CL410M



GRACEFUL GRAY
UMOGRGR4CL410G



GRACEFUL GRAY MATTE
UMOGRGR4CL410M



TAUPE
UMOTAUP4CL410G






TAUPE MATTE
UMOTAUP4CL410M

CLASSICO

(4 OF 5) CERAMIC WALL TILES

UMORE

SIZES

	Nominal Size	Actual Size	Thickness	Color	Finish	Sq. Ft. / Carton	Pcs / Carton
	3"x6"	3"x6"	0.25"	Simply White, Graceful Gray, Taupe	Gloss or Matte	10 sqft	80
	3"x12"	3"x12"	0.25"	Simply White, Graceful Gray, Taupe	Gloss or Matte	12.59 sqft	50
	4"x10"	4"x10"	0.25"	Simply White, Graceful Gray, Taupe	Gloss or Matte	11.248 sqft	38

PRODUCT INFORMATION

Material	Ceramic
Body Color	Standard
Edge	Pressed / Lugged
Manufacturing Process	Inkjet Glazed
Country of Origin	Brazil

INSTALLATION

Suggested Grout Line Size	1/8"
Installation Options	Wall Only
Shade Variation	V1 Very Uniform Appearance



PERFORMANCE PROPERTIES

Test	Test Standard	Result
Dynamic Coefficient of Friction	ANSI A137.1-2012 AcuTest™ ANSI/NFSI B101.3-2012	n/a
Water Absorption	ASTM C373-16 ISO 10545-3	Water Resistant (with proper sealant)
PEI Rating	ASTM C1027-09 or ISO 10545-7 (Glazed); ASTM C1243-93 (2015) or ISO 10545-6 (Unglazed)	n/a
Mohs Scratch Hardness	1:Talc 2:Gypsum 3:Calcite 4:Fluorite 5:Apatite 6:Feldspar 7:Quartz 8:Topaz 9:Corundum 10:Diamond	3
Breaking Strength	ASTM C648-04 (2014): ≥275 lbf	n/a
Chemical Resistance	ASTM C650	n/a
Freeze Thaw	ASTM C1026	n/a

APPLICATION

Backsplash	✓	Indoor Wall	✓
Shower Wall	✓	Indoor Floor	✗
Shower Floor	✗	Pool Decking	✗
Submerged (Tub)	✗	Submerged (Pool)	✗
Outdoor	✗	Residential/Commercial Use:	✓

NOTES

Product specifications are subject to variation and tolerances within testing or productions and may vary. Variations in appearance, texture, construction, dimensions, performance, and style may occur and should be considered in product selection.

The product specifications listed reflect data from the manufacturer or from laboratory testing performed under specific testing conditions. As such it does not represent all conditions under which the products may be used or subjected.

For information on performance standards and/or suitability please consult the ANSI, ASTM, or Tile Council of North America resources.

