

# UMORE



SALERNO  
CERAMIC WALL TILES



## LACE



LACE 3X12  
UMOLACESAL312G

LACE 4X16  
UMOLACESAL416G

LACE MATTE 2.5X16  
UMOLACESAL2516M

## PEARL



PEARL 3X12  
UMOPEARSAL312G

PEARL 4X16  
UMOPEARSAL416G




PEARL MATTE 2.5X16  
UMOPEARSAL2516M

## CARBON



CARBON MATTE 2.5X16  
UMOCARBSAL2516M

### SIZES

	Nominal Size	Actual Size	Thickness	Color	Finish	Sq. Ft. / Carton	Pcs / Carton
	3"x12"	3"x12"	0.30"	Lace, Pearl	Gloss	5.28 sqft	22
	2.5"x16"	2.50"x15.50"	0.30"	Lace, Pearl, Carbon	Matte	8.40 sqft	30
	4"x16"	4"x16"	0.30"	Lace, Pearl	Gloss	10.32 sqft	24

### PRODUCT INFORMATION

Material	Ceramic
Body Color	Standard
Edge	Pressed
Manufacturing Process	Glazed
Country of Origin	Spain

### INSTALLATION

Suggested Grout Line Size	1/16"
Installation Options	Wall Only
Shade Variation	V0 Very Uniform Appearance



### PERFORMANCE PROPERTIES

Test	Test Standard	Result
Dynamic Coefficient of Friction	ANSI A137.1-2012 AcuTest™ ANSI/NFSI B101.3-2012	n/a
Water Absorption	ASTM C373-16 ISO 10545-3	3-8%
PEI Rating	ASTM C1027-09 or ISO 10545-7 (Glazed); ASTM C1243-93 (2015) or ISO 10545-6 (Unglazed)	n/a
Mohs Scratch Hardness	1:Talc 2:Gypsum 3:Calcite 4:Fluorite 5:Apatite 6:Feldspar 7:Quartz 8:Topaz 9:Corundum 10:Diamond	n/a
Breaking Strength	ASTM C648-04 (2014): ≥275 lbf	n/a
Chemical Resistance	ASTM C650	n/a
Freeze Thaw	ASTM C1026	n/a

### APPLICATION

Backsplash	✓	Indoor Wall	✓
Shower Wall	✓	Indoor Floor	✗
Shower Floor	✗	Pool Decking	✗
Submerged (Tub)	✗	Submerged (Pool)	✗
Outdoor	✗	Residential/Commercial Use:	✓

### NOTES

Product specifications are subject to variation and tolerances within testing or productions and may vary. Variations in appearance, texture, construction, dimensions, performance, and style may occur and should be considered in product selection.

The product specifications listed reflect data from the manufacturer or from laboratory testing performed under specific testing conditions. As such it does not represent all conditions under which the products may be used or subjected.

For information on performance standards and/or suitability please consult the ANSI, ASTM, or Tile Council of North America resources.

