

UMORE



TIVOLI
PORCELAIN TILES



15X30 TILE



PEWTER
UMOPEWTTIV1530M



DARK PEWTER
UMODAPETIV1530M



MIDNIGHT
UMOMIDNTIV1530M

30X30 TILE



PEWTER
UMOPEWTTIV3030M



DARK PEWTER
UMODAPETIV3030M



MIDNIGHT
UMOMIDNTIV3030M


10X11 HEX MOSAIC



PEWTER
UMOPEWTTIVHEXM



DARK PEWTER
UMODAPETIVHEXM



MIDNIGHT
UMOMIDNTIVHEXM

SIZES

| | Nominal Size | Actual Size | Thickness | Color | Finish | Sq. Ft. / Carton | Pcs / Carton |
|--|-----------------------|-------------------------------|-----------|-------------------------------|--------|------------------|--------------|
|  | 15"x30" | 14.50"x29.50" | 9.5mm | Pewter, Dark Pewter, Midnight | Matte | 11.69 sqft | 4 |
|  | 30"x30" | 29.20"x29.20" | 9.5mm | Pewter, Dark Pewter, Midnight | Matte | 11.92 sqft | 2 |
|  | 10"x11" Hex Mosaic | 9.80"x11.00" Sheet 3" Chip | 9.5mm | Pewter, Dark Pewter, Midnight | Matte | n/a | 6 |


PRODUCT INFORMATION

| | |
|-----------------------|-----------------------------------|
| Material | Porcelain |
| Body Color | Standard |
| Edge | Tile: Rectified / Mosaic: Pressed |
| Manufacturing Process | Inkjet |
| Country of Origin | Spain |

INSTALLATION

Suggested Grout Line Size 1/16", 1/8", or 3/16"

| | |
|----------------------|--------------------------|
| Installation Options | Floor/Wall |
| Shade Variation | V3 Moderate Variation |



PERFORMANCE PROPERTIES

| Test | Test Standard | Result |
|---------------------------------|--|---------------------------------------|
| Dynamic Coefficient of Friction | ANSI A137.1-2012 AcuTest™ ANSI/NFSI B101.3-2012 | ≥0.42 |
| Water Absorption | ASTM C373-16 ISO 10545-3 | ≤0.5% (Impervious) |
| PEI Rating | ASTM C1027-09 or ISO 10545-7 (Glazed); ASTM C1243-93 (2015) or ISO 10545-6 (Unglazed) | 3 Dark Pewter: 4 |
| Mohs Scratch Hardness | 1:Talc 2:Gypsum 3:Calcite 4:Fluorite 5:Apatite 6:Feldspar 7:Quartz 8:Topaz 9:Corundum 10:Diamond | 6 Dark Pewter: 7 |
| Breaking Strength | ASTM C648-04 (2014): ≥275 lbf | >275 |
| Chemical Resistance | ASTM C650 | Class B- 1 Dark Pewter: Class A- 0 |
| Freeze Thaw | ASTM C1026 | Resistant |

APPLICATION

| | | | |
|-----------------|---|-----------------------------|---|
| Backsplash | ✓ | Indoor Wall | ✓ |
| Shower Wall | ✓ | Indoor Floor | ✓ |
| Shower Floor | ✓ | Pool Decking | ✓ |
| Submerged (Tub) | ✓ | Submerged (Pool) | ✗ |
| Outdoor | ✓ | Residential/Commercial Use: | ✓ |

NOTES

Product specifications are subject to variation and tolerances within testing or productions and may vary. Variations in appearance, texture, construction, dimensions, performance, and style may occur and should be considered in product selection.

The product specifications listed reflect data from the manufacturer or from laboratory testing performed under specific testing conditions. As such it does not represent all conditions under which the products may be used or subjected.

For information on performance standards and/or suitability please consult the ANSI, ASTM, or Tile Council of North America resources.

